

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-076673

(43)Date of publication of application : 20.03.1995

(51)Int.Cl.

C09J 7/02
C09J 7/02
C09J 7/02
C09J 7/02

(21)Application number : 05-246336

(71)Applicant : OJI KAKO KK

(22)Date of filing : 07.09.1993

(72)Inventor : ONDA MASAMI

(54) TACKY TAPE

(57)Abstract:

PURPOSE: To obtain a tacky tape capable of being retreated while being applied to a container made of foamed polystyrene, comprising a specific constitution composed of a polystyrenic resin film as a base.

CONSTITUTION: A shellac layer and a release agent layer comprising a long- chain alkyl-containing polymer (e.g. polystearyl acrylate) are successively laminated to one side of a substrate made of a polystyrenic resin film (preferably stretched film) and a tacky agent layer is laminated to the other side of the substrate to provide the objective product. The substrate is preferably subjected to adhesion improving treatment such as corona discharge treatment before the shellac layer is formed. The tacky agent layer is preferably formed by blending a rubber-based tacky agent such as natural rubber-based tacky agent with a softener, an aging inhibitor, etc., dissolving the mixture in a solvent such as n-hexane not to dissolve the substrate to provide a tacky agent composition, applying the tacky agent composition.

LEGAL STATUS

[Date of request for examination] 09.02.2000

[Date of sending the examiner's decision of rejection] 26.03.2002

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]